

Model	Flow (L/min)	Voltage (V)	Frequency (Hz)	Power (W)	Current (A)	Speed (RPM)	Air Volume (m ³ /h)	Protection (IP)	Noise (dB)	Authentication	Remarks
AH0608T-CA1	3-60	115V 1PH	50/60	45/37	0.6/0.5	2850/3450	457/553	54	42/48	CE	Temperature protection
AH0608T-CA2		230V 1PH	50/60	45/37	0.27/0.23	2850/3450	457/553	54	42/48	CE	
AH0608T-CA3		380V 1PH	50/60	30/25	0.16/0.14	2850/3450	457/553	54	42/48	CE	
AH0608T-CD1		12V DC	--	12	1.0	2700	445	68	40	CE	Soft Start and Waterproof Brushless and locked rotor protection
AH0608T-CD2		24V DC	--	12	0.5	2700	445	68	40	CE	

Model	Flow (L/min)	Voltage (V)	Frequency (Hz)	Power (W)	Current (A)	Speed (RPM)	Air Volume (m ³ /h)	Protection (IP)	Noise (dB)	Authentication	Remarks
AH0608LT-CA1	3-60	115V 1PH	50/60	90/74	1.2/1	2850/3450	914/1106	54	42/48	CE	Temperature protection
AH0608LT-CA2		230V 1PH	50/60	90/74	0.54/0.46	2850/3450	914/1106	54	42/48	CE	
AH0608LT-CA3		380V 1PH	50/60	60/50	0.32/0.28	2850/3450	914/1106	54	42/48	CE	
AH0608LT-CD1		12V DC	--	24	2.0	2700	890	68	40	CE	Soft Start and Waterproof Brushless and locked rotor protection
AH0608LT-CD2		24V DC	--	24	1.0	2700	890	68	40	CE	

Model	Flow (L/min)	Voltage (V)	Frequency (Hz)	Power (W)	Current (A)	Speed (RPM)	Air Volume (m ³ /h)	Protection (IP)	Noise (dB)	Authentication	Remarks
AH1012-CA1	20-100	115V 1PH	50/60	60/58	0.8/0.74	1300/1550	1500	54	55	CE	Temperature protection
AH1012-CA2		230V 1PH	50/60	60/58	0.42/0.36	1300/1550	1500	54	55	CE	
AH1012-3P-CA2		230V 3PH	50/60	80	0.45	2200	1500	54	60	CE	
AH1012-3P-CA3		400V 3PH	50/60	80	0.22	2600	1500	54	60	CE	
AH1012-CD1		12V DC	--	192	16	2000	1500	--	60	CE	
AH1012-CD2		24V DC	--	192	8	2400	1500	--	60	CE	
<i>12V and 24V DC uses carbon brush motor, approximate serice life limit 2000 hours</i>											

Model	Flow (L/min)	Voltage (V)	Frequency (Hz)	Power (W)	Current (A)	Speed (RPM)	Air Volume (m ³ /h)	Protection (IP)	Noise (dB)	Authentication	Remarks
AH1418-CA2	30-100	230V 3PH	50/60	150/180	0.8/0.7	1380/1550	3200/3800	54	62	CE	Temperature protection
AH1418-CA3		400V 3PH	50/60	150/180	0.4/0.36	1380/1550	3200/3800	54	62	CE	
AH1418-CA4		440V 3PH	50/60	200/260	0.4/0.43	1380/1550	3200/3800	54	62	CE	

Model	Flow (L/min)	Voltage (V)	Frequency (Hz)	Power (W)	Current (A)	Speed (RPM)	Air Volume (m ³ /h)	Protection (IP)	Noise (dB)	Authentication	Remarks
AH1428-CA2	30-150	230V 3PH	50/60	150/180	0.8/0.7	1380/1550	3200/3800	54	62	CE	Temperature protection
AH1428-CA3		400V 3PH	50/60	150/180	0.4/0.36	1380/1550	3200/3800	54	62	CE	
AH1428-CA4		440V 3PH	50/60	200/260	0.4/0.43	1380/1550	3200/3800	54	62	CE	