


XV-2U

STANDARD EUROPEAN MOTOR ø36.5 FLANGE - TAPER SHAFT

X	2	U	51	02	E	P	O	A
---	---	---	----	----	---	---	---	---

Series	X	series XV
Group	2	group 2
Category	U	unidirectional motor
Displacement	51	17
Flange	02	Ø36.5 STANDARD EUROPEAN right rotation
Shaft	E	CO001 - Tapered 1:8 - Ø17.4 - M12x1.5 - key thk.4
Body	IN	P inlet - Ø40 Ø20 M8
	OUT	O outlet - Ø30 Ø13.5 M6
Cover	A	standard



XU201

Technical data table


TYPE	Displacement	Max. Pressure		CODE																	
	cm3/rev	P1 bar	P3 bar	 Left rotation								 Right rotation									
XV-2U/04	4,20	260	300	X	2	U	41	01	E	O	O	A	X	2	U	41	02	E	O	O	A
XV-2U/06	6,00	260	300	X	2	U	43	01	E	O	O	A	X	2	U	43	02	E	O	O	A
XV-2U/09	8,40	260	300	X	2	U	45	01	E	O	O	A	X	2	U	45	02	E	O	O	A
XV-2U/11	10,80	260	300	X	2	U	47	01	E	O	O	A	X	2	U	47	02	E	O	O	A
XV-2U/14	14,40	250	290	X	2	U	49	01	E	P	O	A	X	2	U	49	02	E	P	O	A
XV-2U/17	16,80	230	270	X	2	U	51	01	E	P	O	A	X	2	U	51	02	E	P	O	A
XV-2U/19	19,20	210	250	X	2	U	53	01	E	P	O	A	X	2	U	53	02	E	P	O	A
XV-2U/22	22,80	200	240	X	2	U	55	01	E	P	O	A	X	2	U	55	02	E	P	O	A
XV-2U/26	26,20	170	210	X	2	U	57	01	E	Q	P	A	X	2	U	57	02	E	Q	P	A
XV-2U/30	30,00	160	200	X	2	U	59	01	E	Q	P	A	X	2	U	59	02	E	Q	P	A
XV-2U/34	34,20	150	190	X	2	U	61	01	E	Q	P	A	X	2	U	61	02	E	Q	P	A
XV-2U/40	39.60	140	180	X	2	U	63	01	E	Q	P	A	X	2	U	63	02	E	Q	P	A

P1) Max. working pressure - P3) Max. peak pressure

For heavy-duty applications, it is recommended to check the admissible torque of the shaft

Dimensions table

TYPE	Weight	A	B	C	D	E	F	D	E	F
	kg	mm	mm	mm	IN			OUT		
XV-2U/04	2,200	87,2	41,7	77,2	ø13,5	30	M6x1	ø13,5	30	M6x1
XV-2U/06	2,300	90,2	43,2	80,2	ø13,5	30	M6x1	ø13,5	30	M6x1
XV-2U/09	2,400	94,2	45,2	84,2	ø13,5	30	M6x1	ø13,5	30	M6x1
XV-2U/11	2,500	98,2	47,2	88,2	ø13,5	30	M6x1	ø13,5	30	M6x1
XV-2U/14	2,700	104,2	50,2	94,2	ø13,5	30	M6x1	ø20	40	M8X1,25
XV-2U/17	2,800	108,2	52,2	98,2	ø13,5	30	M6x1	ø20	40	M8X1,25
XV-2U/19	2,900	112,2	54,2	102,2	ø13,5	30	M6x1	ø20	40	M8X1,25
XV-2U/22	3,050	118,2	57,2	108,2	ø13,5	30	M6x1	ø20	40	M8X1,25
XV-2U/26	3,150	122,2	59,2	112,2	ø20	40	M8X1,25	ø23,5	40	M8X1,25
XV-2U/30	3,400	130,2	63,2	120,2	ø20	40	M8X1,25	ø23,5	40	M8X1,25
XV-2U/34	3,600	137,2	66,7	127,2	ø20	40	M8X1,25	ø23,5	40	M8X1,25
XV-2U/40	3,800	146,2	71,2	136,2	ø20	40	M8X1,25	ø23,5	40	M8X1,25



T.1 = 54÷58.9 [Nm] - screw tightening torque M10

T.3 = 40 [Nm] - torque wrench setting 19

T.2 = 233.2 [Nm] - admissible shaft torque (N.B. When choosing a shaft, always check the admissible torque).

Table of variations

XV-2U

ø36.5 FLANGE

ø36.5 FLANGE				Shaft				Cover			
Left rotation		Right rotation						Left rotation		Right rotation	
	01		02	CI001 - Parallel T.2 = 44.1 [Nm]	A	CI002 - Parallel T.2 = 67.5 [Nm]	B				A
	03		04	CO001 - Tapered T.2 = 233.2 [Nm]	E	CO002 - Tapered T.2 = 233.2 [Nm]	F				B
	05		06	SCF02 - Splined T.2 = 86.1 [Nm]	G	SCF03 - Splined T.2 = 86.1 [Nm]	H				C
	07		08	SCF04 - Splined T.2 = 67.1 [Nm]	I	SCF01 - Splined T.2 = 86.2 [Nm]	L				D

Displacement	
TYPE	CODE
XV-2U/04	41
XV-2U/06	43
XV-2U/09	45
XV-2U/11	47
XV-2U/14	49
XV-2U/17	51
XV-2U/19	53
XV-2U/22	55
XV-2U/26	57
XV-2U/30	59
XV-2U/34	61
XV-2U/40	63

Standard bodies						
Displacement cm3/rev		Standard threads				
4	O - O	S - R	B - B	L - M	Z - Z	
6	O - O	S - R	B - B	L - M	Z - Z	
9	O - O	S - R	B - B	L - M	Z - Z	
11	O - O	S - R	B - B	L - M	Z - Z	
14	P - O	S - R	C - B	L - M	Z - Z	
17	P - O	S - R	C - B	L - M	Z - Z	
19	P - O	S - R	C - B	L - M	Z - Z	
22	P - O	S - R	C - B	L - M	Z - Z	
26	Q - P	S - R	D - C	L - M	Z - Z	
30	Q - P	S - S	D - C	L - M	Z - Z	
34	Q - P	S - S	D - C	L - M	Z - Z	
40	Q - P	S - S	D - C	L - M	Z - Z	

Table showing standard flange and thread combinations available in stock

			N
Internal drainage			
			O
External drainage			

Body (threads/flanges)											
	A		B		C		D		E		F
	H		I		L		M		N		O
	Q		R		S		T		U		V
Closed Body										Z	